



RadiForce® GS320

54 cm (21.3") Monochrome LCD Monitor



Optimum Image, Same Image.



12:41



In continuously striving for the highest-level of safety and quality while contributing to long-term cost reduction, EIZO offers a five-year limited warranty.



*Bundled ScreenManager Pro for medical required.

Model Variations	GS320-CL: Clear Base GS320-CL-P: Pairing	USB Ports / USB Standard	1 upstream, 2 downstream / Standard Rev. 2.0
Cabinet Color	Black	Power Requirements	AC100 - 120V, 200 - 240V: 50/60 Hz
Panel	54 cm (21.3") TFT Monochrome LCD Panel (IPS)	Power Consumption	115 W
Active Display Size (H x V)	324.8 x 433.1 mm	Power Save Mode	Less than 3 W
Viewable Image Size	Diagonal: 541 mm	Sensor	Backlight Sensor
Native Resolution	1536 x 2048	Power Management	DVI DMPM
Pixel Pitch	0.2115 x 0.2115 mm	OSD Languages	English, French, German, Italian, Japanese, Simplified Chinese, Spanish, Swedish, Traditional Chinese
Grayscale Tones	1,024 from a palette of 8,161 tones	Height Adjustment Range	82 mm
Viewing Angles (H,V)	170° / 170°	Pivot	90°
Brightness	1000 cd/m ² (typical)	Tilt / Swivel	40° Up / 35° Right, 35° Left
Recommended Brightness for Calibration	450 cd/m ²	Dimensions (W x H x D)	With Stand: 376 x 522.5 - 604.5 x 208.5 mm Without Stand: 376 x 500 x 92 mm
Brightness Uniformity	DUE Function	Net Weight	With Stand: 9.9 kg Without Stand: 6.9 kg
Contrast Ratio	850: 1 (typical)	Hole Spacing	VESA standard (100 x 100 mm)
Response Time	23 ms (typical)	Certifications and Standards	CE (Medical Device Directive), TÜV/GM (EN60601-1), cTUVus (UL60601-1, CSA C22.2 No. 601-1), CB (IEC60601-1), VCCI-B, FCC-B, Canadian ICES-003-B, c-Tick, FDA 510(k)
Scanning Frequency (H,V)	31 - 100 kHz, 48 - 71.5 Hz (VGA Text: 69 - 71 Hz) Frame synchronous mode: 59 - 61 Hz	Supplied Accessories	AC power cord, user's manual, signal cable (DVI-D~DVI-D), USB cable, EIZO LCD Utility Disk (ScreenManager Pro for Medical software), warranty card
Dot Clock	165 MHz		
Input Signals	DVI Standard 1.0		
Input Terminal	DVI-D 24 pin		

EIZO NANAO CORPORATION

H u .n

Phone +81-76-277-6792 Fax +81-76-277-6793

radiforce.com

Copyright © 2006 EIZO NANAO CORPORATION. All rights reserved.

060618B